SETTINGLIST FORK PRO COMPONENTS

Artikelnummer:	55182T91 Pro 1	System:	SPLIT FORK
Modellbezeichnung: (ohne Jahresangabe)	890 Duke R	Gabeltyp:	APEX PRO 7500

	Fahrer Komfort	STANDARD	Fahrer Sport	volle Nutzlast
Druckstufendämpfung (Klicks offen)	16	12	9	
Zugstufendämpfung (Klicks offen)	16	12	9	
Preload Adjuster (im Uhrzeigersinn)	1	2	3	

Ölmenge (Standard)	370	ml
Ölmenge (min-max)	350-400	ml

Öl Type	48601166
Öl Viskosität	SAE4
Federweg	130 mm
Gabellänge	

Feder	Gewicht Fahrer	Federrate	Feder Bezeichnung	Federlänge mit Vorspannbüchse	Teilenummer
Feder weicher	65-75 kg	8.0 N/mm	305.260.00.80	262 mm	97010036
Feder STANDARD	75-85 kg	8.5 N/mm	305.260.00.85	262 mm	97010037
Feder härter	85-95 kg	9.0 N/mm	305.260.00.90	262 mm	97010031

Gabelbein Druckstufe (Links)

Cartridge Art. Nr.			
Stk	**Druckstufe Midvalve**	**Stk**	**Zugstufe Midvalve**
1	6x10x0,30	1	8x20x0,40
1	6x12x0,10		
1	6x14x0,10		
2	6x16x0,10		
2	6x18x0,10		
3	6x20x0,15		

Wechselventil Hubhöhe	2 mm
Wechselventil Feder Art.Nr.	48600382
Kolben Midvalve Art.Nr.	48602178
Tap Art.Nr.	43571006
Nadel Art.Nr.	48600671
Mutter Midvalve Art.Nr.	43571007

Stk	**Druckstufe Basevalve**	**Stk**	**Zugstufe Basevalve**
1	6x11x0,30	1	8x20x0,40
1	6x14x0,15		
1	6x16x0,15		
1	6x18x0,15		
5	6x20x0,15		

Wechselventil Hubhöhe	2 mm
Wechselventil Feder Art.Nr.	48600611
Kolben Basevalve Art.Nr.	48602003
Mutter Art.Nr.	43570402

Gabelbein Zugstufe (Rechts)

Cartridge Art. Nr.			
Stk	**Druckstufe Midvalve**	**Stk**	**Zugstufe Midvalve**
1	8x20x0,40	1	6x10x0,30
		1	6x12x0,15
		1	6x14x0,15
		1	6x16x0,15
		1	6x18x0,15
		2	T6x20x0,20

Wechselventil Hubhöhe	2 mm
Wechselventil Feder Art.Nr.	4860059
Kolben Midvalve Art.Nr.	48602178
Tap Art.Nr.	43571005
Nadel Art.Nr.	48600671
Mutter Midvalve Art.Nr.	50180523

Stk	**Druckstufe Basevalve**	**Stk**	**Zugstufe Basevalve**
1	6x11x0,30	1	8x20x0,40
1	6x14x0,15		
1	6x16x0,15		
1	6x18x0,15		
5	6x20x0,15		

Wechselventil Hubhöhe	2 mm
Wechselventil Feder Art.Nr.	48600611
Kolben Basevalve Art.Nr.	48602003
Mutter Art.Nr.	43570402

Bemerkung

Alternativsettingliste: Pro 1

			Ersteller:	Thomas Berger
55182T91ASLP1_a_Serie_SL	Templ.: AM_SPLIT_Fork_SL_V1.6	Seite 1/1	Datum:	2.12.2019

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.

Husqvarna MOTORCYCLES KTM

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.

SETTINGLIST FORK PRO COMPONENTS

Article-No.:	55182T91 Pro 1	System:	SPLIT FORK
Model description: (without year declaration)	890 Duke R	Type:	APEX PRO 7500

	driving comfort	STANDARD	driving sport	max.payload
Compression damping (clicks open or marking)	16	12	9	
Rebound damping (clicks open or marking)	16	12	9	
Preload Adjuster (clock wise)	1	2	3	

oil capacity (standard)	370	ml
oil capacity (min-max)	350-400	ml

Oil type	48601166
Oil viscosity	SAE4
Fork stroke	130 mm
Fork length	

Spring	Riders weight	Spring rate	Spring description	Spring length with preload spacer	Part.-No.
Spring softer	65-75 kg	8.0 N/mm	305.260.00.80	262 mm	97010036
Spring STANDARD	75-85 kg	8.5 N/mm	305.260.00.85	262 mm	97010037
Spring harder	85-95 kg	9.0 N/mm	305.260.00.90	262 mm	97010031

Fork leg compression (left side)

Cartridge Art. No.			
Qty	**Compression Midvalve**	**Qty**	**Rebound Midvalve**
1	6x10x0,30	1	8x20x0,40
1	6x12x0,10		
1	6x14x0,10		
2	6x16x0,10		
2	6x18x0,10		
3	6x20x0,15		

Check valve lift height	2 mm
Check valve spring Art. No.	48600382
Piston Midvalve Art. No.	48602178
Tap art. No.	43571006
Needle Art.No.	48600671
Nut Art. No.	43571007

Qty	**Compression Basevalve**	**Qty**	**Rebound Basevalve**
1	6x11x0,30	1	8x20x0,40
1	6x14x0,15		
1	6x16x0,15		
1	6x18x0,15		
5	6x20x0,15		

Check valve lift height	2 mm
Check valve spring Art.No.	48600611
Piston Basevalve Art.No.	48602003
Nut Basevalve Art.No.	43570402

Fork leg rebound (right side)

Cartridge Art. No.			
Qty	**Compression Midvalve**	**Qty**	**Rebound Midvalve**
1	6x20x0,40	1	6x10x0,30
		1	6x12x0,15
		1	6x14x0,15
		1	6x16x0,15
		1	6x18x0,15
		2	T6x20x0,20

Check valve lift height	2 mm
Check valve spring Art. No.	4860059
Piston Midvalve Art. No.	48602178
Tap art. No.	43571005
Needle Art.No.	48600671
Nut Art. No.	50180523

Qty	**Compression Basevalve**	**Qty**	**Rebound Basevalve**
1	6x11x0,30	1	8x20x0,40
1	6x14x0,15		
1	6x16x0,15		
1	6x18x0,15		
5	6x20x0,15		

Check valve lift height	2 mm
Check valve spring Art.No.	48600611
Piston Basevalve Art.No.	48602003
Nut Basevalve Art.No.	43570402

Note

Alternativsettingliste: Pro 1

			Created by:	Thomas Berger
55182T91ASLP1_a_Serie_SL	Templ.: AM_SPLIT_Fork_SL_V1.6	Page 1/1	Date:	2.12.2019

Husqvarna MOTORCYCLES KTM

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.