SETTINGLIST FORK PRO COMPONENTS

Artikelnummer:	55182T01	System:	SPLIT FORK
Modellbezeichnung: (ohne Jahresangabe)	1290 Super Duke R	Gabeltyp:	APEX PRO 7500

	Fahrer Komfort	STANDARD	Fahrer Sport	volle Nutzlast
Druckstufendämpfung (Klicks offen)	16	12	9	
Zugstufendämpfung (Klicks offen)	16	12	9	
Preload Adjuster (im Uhrzeigersinn)	2	4	4	

Ölmenge (Standard)	550	ml
Ölmenge (min-max)		ml

Öl Type	48601166
Öl Viskosität	SAE 4
Federweg	130 mm
Gabellänge	765 mm

Feder	Gewicht Fahrer	Federrate	Feder Bezeichnung	Federlänge mit Vorspannbüchse	Teilenummer
Feder weicher	65-75 kg	9,0 N/mm	305.260.00.090	262 mm	97010031
Feder STANDARD	75-85 kg	9,5 N/mm	305.260.00.095	262 mm	97010032
Feder härter	85-95 kg	10 N/mm	305.260.00.100	262 mm	97010033

Gabelbein Druckstufe (Links)

Cartridge Art. Nr.:

Stk	Druckstufe Midvalve	Stk	Zugstufe Midvalve
1	6x9x0,30	1	8x20x0,40
1	6x12x0,10		
1	6x14x0,10		
2	6x16x0,10		
2	6x18x0,10		
3	6x20x0,15		

Wechselventil Hubhöhe	2 mm
Wechselventil Feder Art.Nr.	48600382
Kolben Midvalve Art.Nr.	48602178
Tap Art.Nr.	43571006
Nadel Art.Nr.	48600671
Mutter Midvalve Art.Nr.	43571007

Stk	Druckstufe Basevalve	Stk	Zugstufe Basevalve
1	6x11x0,30	1	8x20x0,40
1	6x14x0,15		
1	6x16x0,15		
1	6x18x0,15		
5	6x20x0,15		

Wechselventil Hubhöhe	2 mm
Wechselventil Feder Art.Nr.	48600611
Kolben Basevalve Art.Nr.	48602003
Mutter Art.Nr.	43570402

Gabelbein Zugstufe (Rechts)

Cartridge Art. Nr.:

Stk	Druckstufe Midvalve	Stk	Zugstufe Midvalve
1	8x20x0,40	1	6x14x0,25
		1	6x9,5x0,30
		1	6x12x0,15
		1	6x14x0,15
		1	6x16x0,15
		1	6x18x0,20
		3	T6x20x0,20

Wechselventil Hubhöhe	2 mm
Wechselventil Feder Art.Nr.	48600059
Kolben Midvalve Art.Nr.	48602178
Tap Art.Nr.	43571005
Nadel Art.Nr.	48600671
Mutter Midvalve Art.Nr.	50180523

Stk	Druckstufe Basevalve	Stk	Zugstufe Basevalve
1	6x11x0,30	1	8x20x0,40
1	6x14x0,15		
1	6x16x0,15		
1	6x18x0,15		
5	6x20x0,15		

Wechselventil Hubhöhe	2 mm
Wechselventil Feder Art.Nr.	48600611
Kolben Basevalve Art.Nr.	48602003
Mutter Art.Nr.	43570402

Bemerkung

			Ersteller:	10.09.2019
55182T01_a_Serie_SL	Templ.: AM_SPLIT_Fork_SL_V1.6	Seite 1/1	Datum:	Thomas Berger

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.

SETTINGLIST FORK PRO COMPONENTS

Article-No.:	55182T01	System:	SPLIT FORK
Model description: (without year declaration)	1290 Super Duke R	Type:	APEX PRO 7500

	driving comfort	STANDARD	driving sport	max.payload
Compression damping (clicks open or marking)	16	12	9	
Rebound damping (clicks open or marking)	16	12	9	
Preload Adjuster (clock wise)	2	4	4	

oil capacity (standard)	550	ml
oil capacity (min-max)		ml

Oil type	48601166
Oil viscosity	SAE 4
Fork stroke	130 mm
Fork length	765 mm

Spring	Riders weight	Spring rate	Spring description	Spring length with preload spacer	Part.-No.
Spring softer	65-75 kg	9,0 N/mm	305.260.00.090	262 mm	97010031
Spring STANDARD	75-85 kg	9,5 N/mm	305.260.00.095	262 mm	97010032
Spring harder	85-95 kg	10 N/mm	305.260.00.100	262 mm	97010033

Fork leg compression (left side)

Cartridge Art. No.:

Qty	Compression Midvalve	Qty	Rebound Midvalve
1	6x9x0,30	1	8x20x0,40
1	6x12x0,10		
1	6x14x0,10		
2	6x16x0,10		
2	6x18x0,10		
3	6x20x0,15		

Check valve lift height	2 mm
Check valve spring Art. No.	48600382
Piston Midvalve Art. No.	48602178
Tap art. No.	43571006
Needle Art.No.	48600671
Nut Art. No.	43571007

Qty	Compression Basevalve	Qty	Rebound Basevalve
1	6x11x0,30	1	8x20x0,40
1	6x14x0,15		
1	6x16x0,15		
1	6x18x0,15		
5	6x20x0,15		

Check valve lift height	2 mm
Check valve spring Art.No.	48600611
Piston Basevalve Art.No.	48602003
Nut Basevalve Art.No.	43570402

Fork leg rebound (right side)

Cartridge Art. No.:

Qty	Compression Midvalve	Qty	Rebound Midvalve
1	8x20x0,40	1	6x14x0,25
		1	6x9,5x0,30
		1	6x12x0,15
		1	6x14x0,15
		1	6x16x0,15
		1	6x18x0,20
		3	T6x20x0,20

Check valve lift height	2 mm
Check valve spring Art. No.	48600059
Piston Midvalve Art. No.	48602178
Tap art. No.	43571005
Needle Art.No.	48600671
Nut Art. No.	50180523

Qty	Compression Basevalve	Qty	Rebound Basevalve
1	6x11x0,30	1	8x20x0,40
1	6x14x0,15		
1	6x16x0,15		
1	6x18x0,15		
5	6x20x0,15		

Check valve lift height	2 mm
Check valve spring Art.No.	48600611
Piston Basevalve Art.No.	48602003
Nut Basevalve Art.No.	43570402

Note

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.