

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.

SETTINGLIST FORK

AM

Article number:	34182T01	System:	Air Fork
Modeldescription: (without year declaration)	KTM 125/150 SX HQV TC 125	Type:	XACT PRO 7448

	<i>driving comfort</i>	STANDARD	<i>driving sport</i>	<i>max. payload</i>
Compression damping (clicks open)		18		
Rebound damping (clicks open)		20		

Oil capacity right	375	ml	min/max	-	ml	Oil type	48601166
Grease quantity cartridge left	5	g	min/max	-	ml	Oil viscosity	SAE 4
Oil capacity outertube right	240	ml	min/max	200/300	ml	Fork stroke	309 mm
Oil capacity outertube left	240	ml	min/max	200/300	ml	Fork length	950 mm

Spring	Riders weight	pressure pos. chamber top	pressure neg. chamber bottom
<i>Spring soft opt. 2</i>			
<i>Spring soft opt. 1</i>	45-55 kg	8.2 bar	9.2 bar
Spring STANDARD	55-65 kg	8.6 bar	9.6 bar
<i>Spring hard opt. 1</i>	65-75 kg	9 bar	10 bar
<i>Spring hard opt. 2</i>	75-85 kg	9.4 bar	10.4 bar

Reservoir - Spring-Rate	18 N/mm
Reservoir spring Art.No.	48601851

Shims piston compression

Qty	Compression	Qty	Rebound
1	6x25x1.50	1	6x18x0.40
1	6x12x0.10	3	6x18x0.25
1	6x13x0.10	1	6x10x0.20
1	6x14x0.10	1	48601459
1	6x15x0.10		
1	6x16x0.10		
1	6x17x0.10		
1	6x18x0.10		
1	6x19x0.10		
1	6x20x0.10		
1	6x21x0.10		
1	6x22x0.10		
1	6x23x0.10		
1	6x24x0.10		
1	6x25x0.10		
2	6x28x0.10		
1	6x22x0.10		
6	6x30x0.15		
Nut compression Art.No.		09340601	
Check valve lift height		0 mm	
Check valve spring Art.No.		-	
Piston Art.No.		48602005S	
Piston bleed		0 mm	

Shims piston rebound

Qty	Compression	Qty	Rebound
1	Cone Cage 1.5mm	1	48601917
	48601798	1	6x14x0.20
1	Black Cone 18deg	1	6x16x0.10
	48601801	1	6x20x0.10
1	Spring C=125	1	6x22x0.10
	48601805	1	6x24x0.10
		1	6x26x0.10
		1	6x20x0.10
		3	6x28x0.10
Check valve lift height		0.10 mm	
Check valve spring Art.No.		48601805	
Piston Art.No.		48602014	
Piston bleed		0 mm	

Note

different shim setting from 34182T07

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmusterreife eingetragene vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.



The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.



Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmusterertragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

SETTINGLIST FORK AM

Article number:	34182T03	System:	Air Fork
Modeldescription: (without year declaration)	KTM 250 SX HQV TC 250	Type:	XACT PRO 7448

	<i>driving comfort</i>	STANDARD	<i>driving sport</i>	<i>max. payload</i>
Compression damping (clicks open)		18		
Rebound damping (clicks open)		20		

Oil capacity right	375	ml	min/max	-	ml	Oil type	48601166
Grease quantity cartridge left	5	g	min/max	-	ml	Oil viscosity	SAE 4
Oil capacity outertube right	240	ml	min/max	200/300	ml	Fork stroke	309 mm
Oil capacity outertube left	240	ml	min/max	200/300	ml	Fork length	950 mm

Spring	Riders weight	pressure pos. chamber top	pressure neg. chamber bottom
<i>Spring soft opt. 2</i>	<i>55-65 kg</i>	<i>9.2 bar</i>	<i>10.2 bar</i>
<i>Spring soft opt. 1</i>	<i>65-75 kg</i>	<i>9.6 bar</i>	<i>10.6 bar</i>
Spring STANDARD	75-85 kg	10 bar	11 bar
<i>Spring hard opt. 1</i>	<i>85-95 kg</i>	<i>10.4 bar</i>	<i>11.4 bar</i>
<i>Spring hard opt. 2</i>	<i>95-105 kg</i>	<i>10.8 bar</i>	<i>11.8 bar</i>

Reservoir - Spring-Rate	18 N/mm
Reservoir spring Art.No.	48601851

Shims piston compression			
Qty	Compression	Qty	Rebound
1	6x25x1.50	1	6x18x0.40
1	6x12x0.10	3	6x18x0.25
1	6x13x0.10	1	6x10x0.20
1	6x14x0.10	1	48601459
1	6x15x0.10		
1	6x16x0.10		
1	6x17x0.10		
1	6x18x0.10		
1	6x19x0.10		
1	6x20x0.10		
1	6x21x0.10		
1	6x22x0.10		
1	6x23x0.10		
1	6x24x0.10		
1	6x25x0.10		
1	6x26x0.10		
2	6x28x0.10		
1	6x22x0.10		
6	6x30x0.15		
Nut compression Art.No.	09340601		
Check valve lift height	0 mm		
Check valve spring Art.No.	-		
Piston Art.No.	48602005S		
Piston bleed	0 mm		

Shims piston rebound			
Qty	Compression	Qty	Rebound
1	Cone Cage 1.5mm	1	48601917
	48601798	1	6x14x0.20
1	Black Cone 18deg	1	6x16x0.10
	48601801	1	6x20x0.10
1	Spring C=125	1	6x22x0.10
	48601805	1	6x24x0.10
		1	6x26x0.10
		1	6x20x0.10
		3	6x28x0.10
Check valve lift height	0.10 mm		
Check valve spring Art.No.	48601805		
Piston Art.No.	48602014		
Piston bleed	0 mm		

Note

different shim setting from 34182T07

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.



Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmusterertragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

SETTINGLIST FORK

AM

Article number:	34182T05	System:	Air Fork
Modeldescription: (without year declaration)	KTM 250 SXF HQV FC 250	Type:	XACT PRO 7448

	<i>driving comfort</i>	STANDARD	<i>driving sport</i>	<i>max. payload</i>
Compression damping (clicks open)		14		
Rebound damping (clicks open)		20		

Oil capacity right	375	ml	min/max	-	ml	Oil type	48601166
Grease quantity cartridge left	5	g	min/max	-	ml	Oil viscosity	SAE 4
Oil capacity outertube right	270	ml	min/max	200/300	ml	Fork stroke	309 mm
Oil capacity outertube left	270	ml	min/max	200/300	ml	Fork length	950 mm

Spring	Riders weight	pressure pos. chamber top	pressure neg. chamber bottom
<i>Spring soft opt. 2</i>	55-65 kg	10.2 bar	10.2 bar
<i>Spring soft opt. 1</i>	65-75 kg	10.4 bar	10.4 bar
Spring STANDARD	75-85 kg	10.6 bar	10.6 bar
<i>Spring hard opt. 1</i>	85-95 kg	10.8 bar	10.8 bar
<i>Spring hard opt. 2</i>	95-105 kg	11.0 bar	11.0 bar

Reservoir - Spring-Rate	20 N/mm
Reservoir spring Art.No.	48601749

Shims piston compression			
Qty	Compression	Qty	Rebound
1	6x25x1.50	1	6x18x0.40
1	6x14x0.10	3	6x18x0.25
1	6x15x0.10	1	6x10x0.20
1	6x16x0.10	1	48601459
1	6x17x0.10		
1	6x18x0.10		
1	6x19x0.10		
1	6x20x0.10		
1	6x21x0.10		
1	6x22x0.10		
1	6x23x0.10		
1	6x24x0.10		
1	6x25x0.10		
1	6x26x0.10		
2	6x28x0.10		
1	6x22x0.10		
6	6x30x0.15		
Nut compression Art.No.	09340601		
Check valve lift height	0 mm		
Check valve spring Art.No.	-		
Piston Art.No.	48602005S		
Piston bleed	0 mm		

Shims piston rebound			
Qty	Compression	Qty	Rebound
1	Cone Cage 1.5mm	1	48601917
	48601798	1	6x14x0.20
1	Black Cone 18deg	1	6x16x0.10
	48601801	1	6x20x0.10
1	Spring C=125	1	6x22x0.10
	48601805	1	6x24x0.10
		1	6x26x0.10
		1	6x20x0.10
		3	6x28x0.10
Check valve lift height	0.10 mm		
Check valve spring Art.No.	48601805		
Piston Art.No.	48602014		
Piston bleed	0 mm		

Note

same shim setting as 34182T07

SETTINGLIST FORK

AM

Article number:	34182T09	System:	Air Fork
Modeldescription: (without year declaration)	KTM 450 SXF HQV FC 450	Type:	XACT PRO 7448

	<i>driving comfort</i>	STANDARD	<i>driving sport</i>	<i>max. payload</i>
Compression damping (clicks open)		18		
Rebound damping (clicks open)		20		

Oil capacity right	375	ml	min/max	-	ml	Oil type	48601166
Grease quantity cartridge left	5	g	min/max	-	ml	Oil viscosity	SAE 4
Oil capacity outertube right	240	ml	min/max	200/300	ml	Fork stroke	309 mm
Oil capacity outertube left	240	ml	min/max	200/300	ml	Fork length	950 mm

Spring	Riders weight	pressure pos. chamber top	pressure neg. chamber bottom
<i>Spring soft opt. 2</i>	<i>55-65 kg</i>	<i>9.7 bar</i>	<i>10.7 bar</i>
<i>Spring soft opt. 1</i>	<i>65-75 kg</i>	<i>10.1 bar</i>	<i>11.1 bar</i>
Spring STANDARD	75-85 kg	10.5 bar	11.5 bar
<i>Spring hard opt. 1</i>	<i>85-95 kg</i>	<i>10.9 bar</i>	<i>11.9 bar</i>
<i>Spring hard opt. 2</i>	<i>95-105 kg</i>	<i>11.3 bar</i>	<i>12.3 bar</i>

Reservoir - Spring-Rate	20 N/mm
Reservoir spring Art.No.	48601749

Shims piston compression

Qty	Compression	Qty	Rebound
1	6x25x1.50	1	6x18x0.40
1	6x12x0.10	3	6x18x0.25
1	6x13x0.10	1	6x10x0.20
1	6x14x0.10	1	48601459
1	6x15x0.10		
1	6x16x0.10		
1	6x17x0.10		
1	6x18x0.10		
1	6x19x0.10		
1	6x20x0.10		
1	6x21x0.10		
1	6x22x0.10		
1	6x23x0.10		
1	6x24x0.10		
1	6x25x0.10		
1	6x26x0.10		
2	6x28x0.10		
1	6x22x0.10		
6	6x30x0.15		
Nut compression Art.No.	09340601		
Check valve lift height	0 mm		
Check valve spring Art.No.	-		
Piston Art.No.	48602005S		
Piston bleed	0 mm		

Shims piston rebound

Qty	Compression	Qty	Rebound
1	Cone Cage 1.5mm	1	48601917
	48601798	1	6x14x0.20
1	Black Cone 18deg	1	6x16x0.10
	48601801	1	6x20x0.10
1	Spring C=125	1	6x22x0.10
	48601805	1	6x24x0.10
		1	6x26x0.10
		1	6x20x0.10
		3	6x28x0.10
Check valve lift height	0.10 mm		
Check valve spring Art.No.	48601805		
Piston Art.No.	48602014		
Piston bleed	0 mm		

Note

Airside: 75% Rebound spacer 48601918
[different shim setting from 34182T07](#)

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.



Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmusterreife vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.



Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmusterreife vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

SETTINGLIST FORK

AM

Article number:	34182T51	System:	Air Fork
Modeldescription: (without year declaration)	KTM 125 SX USA Husqvarna TC 125 USA	Type:	XACT PRO 7448

	<i>driving comfort</i>	STANDARD	<i>driving sport</i>	<i>max. payload</i>
Compression damping (clicks open)		15		
Rebound damping (clicks open)		20		

Oil capacity right	375	ml	min/max	-	ml	Oil type	48601166
Grease quantity cartridge left	5	g	min/max	-	ml	Oil viscosity	SAE 4
Oil capacity outertube right	240	ml	min/max	200/300	ml	Fork stroke	309 mm
Oil capacity outertube left	240	ml	min/max	200/300	ml	Fork length	950 mm

Spring	Riders weight	pressure pos. chamber top	pressure neg. chamber bottom
<i>Spring soft opt. 2</i>			
<i>Spring soft opt. 1</i>	45-55 kg	9.9 bar	11.1 bar
Spring STANDARD	55-65 kg	10.3 bar	11.5 bar
<i>Spring hard opt. 1</i>	65-75 kg	10.7 bar	11.9 bar
<i>Spring hard opt. 2</i>	75-85 kg	11.1 bar	12.1 bar

Reservoir - Spring-Rate	12 N/mm
Reservoir spring Art.No.	48601588

Shims piston compression			
Qty	Compression	Qty	Rebound
1	6x25x1.50	1	48601693
2	6x14x0.25	1	6x10x0.20
1	6x16x0.15	1	48601459
1	6x18x0.15		
1	6x20x0.15		
1	6x22x0.15		
1	6x24x0.15		
1	6x26x0.15		
1	6x28x0.15		
1	6x22x0.10		
8	6x30x0.10		
Nut compression Art.No.		09340601	
Check valve lift height		0 mm	
Check valve spring Art.No.		-	
Piston Art.No.		48601451s	
Piston bleed		0 mm	

Shims piston rebound			
Qty	Compression	Qty	Rebound
1	Cone Cage 1.5mm	1	48602030
	48601798	2	6x13x0.15
1	Red Cone 11deg	1	6x14x0.10
	48601799	1	6x15x0.10
1	Spring C=50	1	6x16x0.10
	48601809	1	6x17x0.10
		1	6x18x0.10
		1	6x20x0.10
		1	6x22x0.10
		1	6x24x0.10
		1	6x26x0.10
		1	6x14x0.15
		3	6x28x0.10
Check valve lift height		0 mm	
Check valve spring Art.No.		48601809	
Piston Art.No.		48602014	
Piston bleed		0 mm	

Note

different shim setting from 34182T07

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.



Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmusterreifeintragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

SETTINGLIST FORK

AM

Article number:	34182T53	System:	Air Fork
Modeldescription: (without year declaration)	KTM 250 SX USA Husqvarna TC 250 USA	Type:	XACT PRO 7448

	<i>driving comfort</i>	STANDARD	<i>driving sport</i>	<i>max. payload</i>
Compression damping (clicks open)		15		
Rebound damping (clicks open)		20		

Oil capacity right	375	ml	min/max	-	ml	Oil type	48601166
Grease quantity cartridge left	5	g	min/max	-	ml	Oil viscosity	SAE 4
Oil capacity outertube right	240	ml	min/max	200/300	ml	Fork stroke	309 mm
Oil capacity outertube left	240	ml	min/max	200/300	ml	Fork length	950 mm

Spring	Riders weight	pressure pos. chamber top	pressure neg. chamber bottom
<i>Spring soft opt. 2</i>	<i>55-65 kg</i>	<i>10.5 bar</i>	<i>11.7 bar</i>
<i>Spring soft opt. 1</i>	<i>65-75 kg</i>	<i>10.9 bar</i>	<i>11.1 bar</i>
Spring STANDARD	75-85 kg	11.3 bar	12.5 bar
<i>Spring hard opt. 1</i>	<i>85-95 kg</i>	<i>11.7 bar</i>	<i>12.9 bar</i>
<i>Spring hard opt. 2</i>	<i>95-105 kg</i>	<i>12.1 bar</i>	<i>12.3 bar</i>

Reservoir - Spring-Rate	12N/mm
Reservoir spring Art.No.	48601588

Shims piston compression			
Qty	Compression	Qty	Rebound
1	6x25x1.50	1	48601693
2	6x18x0.25	1	6x10x0.20
1	6x20x0.15	1	48601459
1	6x22x0.15		
1	6x24x0.15		
1	6x26x0.15		
1	6x28x0.15		
1	6x30x0.15		
1	6x22x0.10		
8	6x30x0.10		
Nut compression Art.No.		09340601	
Check valve lift height		0 mm	
Check valve spring Art.No.		-	
Piston Art.No.		48601451s	
Piston bleed		0 mm	

Shims piston rebound			
Qty	Compression	Qty	Rebound
1	Cone Cage 1.5mm	1	48602030
	48601798	2	6x13x0.15
1	Black Cone 18deg	1	6x14x0.10
	48601801	1	6x15x0.10
1	Spring C=75	1	6x16x0.10
	48601808	1	6x17x0.10
		1	6x18x0.10
		1	6x20x0.10
		1	6x22x0.10
		1	6x24x0.10
		1	6x26x0.10
		1	6x14x0.15
		3	6x28x0.10
Check valve lift height		0 mm	
Check valve spring Art.No.		48601808	
Piston Art.No.		48602014	
Piston bleed		0 mm	

Note

different shim setting from 34182T07

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.



Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmusterreifeintragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

SETTINGLIST FORK

AM

Article number:	34182T55	System:	Air Fork
Modeldescription: (without year declaration)	KTM 250 SXF Husqvarna FC 250	Type:	XACT PRO 7448

	<i>driving comfort</i>	STANDARD	<i>driving sport</i>	<i>max. payload</i>
Compression damping (clicks open)		15		
Rebound damping (clicks open)		20		

Oil capacity right	375	ml
Grease quantity cartridge left	5	g
Oil capacity outertube right	240	ml
Oil capacity outertube left	240	ml

min/max	-	ml	Oil type	48601166
min/max	-	ml	Oil viscosity	SAE 4
min/max	200/300	ml	Fork stroke	309 mm
min/max	200/300	ml	Fork length	950 mm

Spring	Riders weight	pressure pos. chamber top	pressure neg. chamber bottom
<i>Spring soft opt. 2</i>	<i>45-55 kg</i>	<i>10.7 bar</i>	<i>11.9 bar</i>
<i>Spring soft opt. 1</i>	<i>55-65 kg</i>	<i>11.1 bar</i>	<i>12.3 bar</i>
Spring STANDARD	65-75 kg	11.5 bar	12.7 bar
<i>Spring hard opt. 1</i>	<i>75-85 kg</i>	<i>11.9 bar</i>	<i>13.1 bar</i>
<i>Spring hard opt. 2</i>	<i>85-95 kg</i>	<i>12.3 bar</i>	<i>13.5 bar</i>

Reservoir - Spring-Rate	12
Reservoir spring Art.No.	48601588

Shims piston compression			
Qty	Compression	Qty	Rebound
1	6x25x1.50	1	48601693
2	6x18x0.25	1	6x10x0.20
1	6x20x0.15	1	48601459
1	6x22x0.15		
1	6x24x0.15		
1	6x26x0.15		
1	6x28x0.15		
1	6x30x0.15		
1	6x22x0.10		
8	6x30x0.10		
Nut compression Art.No.		09340601	
Check valve lift height		0 mm	
Check valve spring Art.No.		-	
Piston Art.No.		48601451s	
Piston bleed		0 mm	

Shims piston rebound			
Qty	Compression	Qty	Rebound
1	Cone Cage 1.5mm	1	48602030
	48601798	2	6x13x0.15
1	Black Cone 18deg	1	6x14x0.10
	48601801	1	6x15x0.10
1	Spring C=75	1	6x16x0.10
	48601808	1	6x17x0.10
		1	6x18x0.10
		1	6x20x0.10
		1	6x22x0.10
		1	6x24x0.10
		1	6x26x0.10
		1	6x14x0.15
		3	6x28x0.10
Check valve lift height		0 mm	
Check valve spring Art.No.		48601808	
Piston Art.No.		48602014	
Piston bleed		0 mm	

Note

different shim setting from 34182T07

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.



Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmusterertragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

SETTINGLIST FORK

AM

Article number:	34182T57	System:	Air Fork
Modeldescription: (without year declaration)	KTM 350 SXF Husqvarna FC 350	Type:	XACT PRO 7448

	<i>driving comfort</i>	STANDARD	<i>driving sport</i>	<i>max. payload</i>
Compression damping (clicks open)		15		
Rebound damping (clicks open)		20		

Oil capacity right	375	ml	min/max	-	ml	Oil type	48601166
Grease quantity cartridge left	5	g	min/max	-	ml	Oil viscosity	SAE 4
Oil capacity outertube right	240	ml	min/max	200/300	ml	Fork stroke	309 mm
Oil capacity outertube left	240	ml	min/max	200/300	ml	Fork length	950 mm

Spring	Riders weight	pressure pos. chamber top	pressure neg. chamber bottom
<i>Spring soft opt. 2</i>	<i>55-65 kg</i>	<i>10.7 bar</i>	<i>11.9 bar</i>
<i>Spring soft opt. 1</i>	<i>65-75 kg</i>	<i>11.1 bar</i>	<i>12.3 bar</i>
Spring STANDARD	75-85 kg	11.5 bar	12.7 bar
<i>Spring hard opt. 1</i>	<i>85-95 kg</i>	<i>11.9 bar</i>	<i>13.1 bar</i>
<i>Spring hard opt. 2</i>	<i>95-105 kg</i>	<i>12.3 bar</i>	<i>13.5 bar</i>

Reservoir - Spring-Rate	12 N/mm
Reservoir spring Art.No.	48601288

Shims piston compression			
Qty	Compression	Qty	Rebound
1	6x25x1.50	1	48601693
2	6x18x0.25	1	6x10x0.20
1	6x20x0.15	1	48601459
1	6x22x0.15		
1	6x24x0.15		
1	6x26x0.15		
1	6x28x0.15		
1	6x30x0.15		
1	6x22x0.10		
8	6x30x0.10		
Nut compression Art.No.		09340601	
Check valve lift height		0 mm	
Check valve spring Art.No.		-	
Piston Art.No.		48601451s	
Piston bleed		0 mm	

Shims piston rebound			
Qty	Compression	Qty	Rebound
1	Cone Cage 1.5mm	1	48602030
	48601798	2	6x13x0.15
1	Black Cone 18deg	1	6x14x0.10
	48601801	1	6x15x0.10
1	Spring C=75	1	6x16x0.10
	48601808	1	6x17x0.10
		1	6x18x0.10
		1	6x20x0.10
		1	6x22x0.10
		1	6x24x0.10
		1	6x26x0.10
		1	6x14x0.15
		3	6x28x0.10
Check valve lift height		0 mm	
Check valve spring Art.No.		48601808	
Piston Art.No.		48602014	
Piston bleed		0 mm	

Note

SETTINGLIST FORK

AM

Article number:	34182T59	System:	Air fork
Modeldescription: (without year declaration)	KTM 450 SXF USA Husqvarna FC 450 USA	Type:	XACT PRO 7448

	<i>driving comfort</i>	STANDARD	<i>driving sport</i>	<i>max. payload</i>
Compression damping (clicks open)		15		
Rebound damping (clicks open)		20		

Oil capacity right	375	ml	min/max	-	ml	Oil type	48601166
Grease quantity cartridge left	5	g	min/max	-	ml	Oil viscosity	SAE 4
Oil capacity outertube right	240	ml	min/max	200/300	ml	Fork stroke	309 mm
Oil capacity outertube left	240	ml	min/max	200/300	ml	Fork length	950 mm

Spring	Riders weight	pressure pos. chamber top	pressure neg. chamber bottom
<i>Spring soft opt. 2</i>	<i>55-65 kg</i>	<i>10.7 bar</i>	<i>11.9 bar</i>
<i>Spring soft opt. 1</i>	<i>65-75 kg</i>	<i>11.1 bar</i>	<i>12.3 bar</i>
Spring STANDARD	75-85 kg	11.5 bar	12.7 bar
<i>Spring hard opt. 1</i>	<i>85-95 kg</i>	<i>11.9 bar</i>	<i>13.1 bar</i>
<i>Spring hard opt. 2</i>	<i>95-105 kg</i>	<i>12.3 bar</i>	<i>13.5 bar</i>

Reservoir - Spring-Rate	12N/mm
Reservoir spring Art.No.	48601588

Shims piston compression

Qty	Compression	Qty	Rebound
1	6x25x1.50	1	48601693
2	6x18x0.25	1	6x10x0.20
1	6x20x0.15	1	48601459
1	6x22x0.15		
1	6x24x0.15		
1	6x26x0.15		
1	6x28x0.15		
1	6x30x0.15		
1	6x22x0.10		
8	6x30x0.10		
Nut compression Art.No.		09340601	
Check valve lift height		0 mm	
Check valve spring Art.No.		-	
Piston Art.No.		48601451s	
Piston bleed		0 mm	

Shims piston rebound

Qty	Compression	Qty	Rebound
1	Cone Cage 1.5mm	1	48602030
	48601798	2	6x13x0.15
1	Black Cone 18deg	1	6x14x0x10
	48601801	1	6x15x0.10
1	Spring C=75	1	6x16x0.10
	48601808	1	6x17x0.10
		1	6x18x0.10
		1	6x20x0.10
		1	6x22x0.10
		1	6x24x0.10
		1	6x26x0.10
		1	6x14x0.15
		3	6x28x0.10
Check valve lift height		0 mm	
Check valve spring Art.No.		48601808	
Piston Art.No.		48602014	
Piston bleed		0 mm	

Note

different shim setting from 34182T07

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.



Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmusterreimtragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.