

PC

KTM 125 SX

GASGAS MC 125

Artikelnummer /
Article number

A460C101Y403200

Reservoir Federrate / reservoir spring rate	18 (48601851)	N/mm	Öl Viskosität / oil viscosity	SAE 4
Ölmenge (Gabelholm) / oil capacity (fork leg)	450	ml	Federweg / fork stroke	309 mm
Ölmenge (Cartridge) / oil capacity (cartridge)	175	ml	Gabellänge / fork length	950 mm

Einstellung / adjustment	Gewicht Fahrer / riders weight	Feder Bezeichnung / spring description	Federlänge mit Büchse / spring length with spacer	Teilenummer / part.-no.
Weich Opt. 2 / soft opt. 2	55-65 kg 121-143 lb	432.485.00.042W	488 mm	91410114
Weich Opt. 1 / soft opt. 1	65-75 kg 143-165 lb	432.485.00.044W	488 mm	91410115
STANDARD	75-85 kg 165-187 lb	432.485.00.046W	488 mm	91410116
Hart Opt. 1 / hard opt. 1	85-95 kg 187-209 lb	432.485.00.048W	488 mm	91410117
Hart Opt. 2 / hard opt. 2	95-105 kg 209-232 lb	432.485.00.050W	488 mm	91410118

Shims Kolben Midvalve /
shims piston midvalve

Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
3	6x22x0,10	1	8x26x0,40
1	6x14x0,10		
1	6x20x0,10		
1	6x18x0,10		
1	6x16x0,10		
1	6x14x0,10		
1	Backplate 6x18x1,50		
1	6x12x0,15		
1	6x14x0,15		
1	6x16x0,15		
1	6x18x0,15		
1	6x20x0,15		
1	6x22x0,15		
1	6x24x0,15		
8	6x26x0,15		
Wechselventil Hubhöhe / check valve lift height		0,4 mm	

[illegible]

PC

KTM 250/300 SX

**Artikelnummer /
Article number**

A460C103Y403200

GASGAS MC 250/300

Reservoir Federrate / reservoir spring rate	18 (48601851)	N/mm	Öl Viskosität / oil viscosity	SAE 4
Ölmenge (Gabelholm) / oil capacity (fork leg)	470	ml	Federweg / fork stroke	309 mm
Ölmenge (Cartridge) / oil capacity (cartridge)	175	ml	Gabellänge / fork length	950 mm

Einstellung / adjustment	Gewicht Fahrer / riders weight	Feder Bezeichnung / spring description	Federlänge mit Büchse / spring length with spacer	Teilenummer / part.-no.
Weich Opt. 2 / soft opt. 2	55-65 kg 121-143 lb	432.485.00.046W	488 mm	91410116
Weich Opt. 1 / soft opt. 1	65-75 kg 143-165 lb	432.485.00.048W	488 mm	91410117
STANDARD	75-85 kg 165-187 lb	432.485.00.050W	488 mm	91410118
Hart Opt. 1 / hard opt. 1	85-95 kg 187-209 lb	432.485.00.052W	488 mm	91410119
Hart Opt. 2 / hard opt. 2	95-105 kg 209-232 lb	432.485.00.054W	488 mm	91410146

Shims Kolben Midvalve /
shims piston midvalve

Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
3	6x22x0,10	1	8x26x0,40
1	6x14x0,10		
1	6x20x0,10		
1	6x18x0,10		
1	6x16x0,10		
1	6x14x0,10		
1	Backplate 6x18x1,50		
1	6x14x0,20		
1	6x16x0,20		
1	6x18x0,20		
1	6x20x0,20		
1	6x22x0,15		
1	6x24x0,15		
6	6x26x0,15		
Wechselventil Hubhöhe / check valve lift height		0,4 mm	

[illegible]

PC

KTM 250 SX-F

GASGAS MC 250F

A460C105Y403200

[illegible]

PC

KTM 350 SX-F

GASGAS MC 350F

A460C107Y403200

Einstellung / adjustment	Gewicht Fahrer / riders weight	Feder Bezeichnung / spring description	Federlänge mit Büchse / spring length with spacer	Teilenummer / part.-no.
Weich Opt. 2 / soft opt. 2	55-65 kg 121-143 lb	432.485.00.048W	488 mm	91410117
Weich Opt. 1 / soft opt. 1	65-75 kg 143-165 lb	432.485.00.050W	488 mm	91410118
STANDARD	75-85 kg 165-187 lb	432.485.00.052W	488 mm	91410119
Hart Opt. 1 / hard opt. 1	85-95 kg 187-209 lb	432.485.00.054W	488 mm	91410146

