

PC

KTM/HQV/GG Cross Country 125 Comfort

**Artikelnummer /
Article number**

A460C171Y403200

Reservoir Federrate / reservoir spring rate	12 (48601588)	N/mm	Öl Viskosität / oil viscosity	SAE 4
Ölmenge (Gabelholm) / oil capacity (fork leg)	400	ml	Federweg / fork stroke	309 mm
Ölmenge (Cartridge) / oil capacity (cartridge)	175	ml	Gabellänge / fork length	950 mm

Einstellung / adjustment	Gewicht Fahrer / riders weight	Feder Bezeichnung / spring description	Federlänge mit Büchse / spring length with spacer	Teilenummer / part.-no.
Weich Opt. 2 / soft opt. 2	55-65 kg 121-143 lb	(43,2) 4,2-485	488 mm	91410114
Weich Opt. 1 / soft opt. 1	65-75 kg 143-165 lb	(43,2) 4,4-485	488 mm	91410115
STANDARD	75-85 kg 165-187 lb	(43,2) 4,6-485	488 mm	91410116
Hart Opt. 1 / hard opt. 1	85-95 kg 187-209 lb	(43,2) 4,8-485	488 mm	91410117
Hart Opt. 2 / hard opt. 2	95-105 kg 209-232 lb	(43,2) 5,0-485	488 mm	91410118

Shims Kolben Midvalve /
shims piston midvalve

Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
1	T6x22x0.10	1	8x26x0.40
2	6x19x0.10	Nut	48601260
1	6x18x0.10		
1	6x16x0.10		
1	6x14x0.10		
1	6x12x0.10		
1	6x10x0.10		
1	48601262		
1	6x12x0.25		
1	6x14x0.15		
1	6x16x0.15		
1	6x18x0.15		
1	6x20x0.15		
1	6x22x0.15		
1	6x24x0.15		
1	6x14x0.10		
3	6x26x0.10		
Wechselventil Hubhöhe / check valve lift height		1,0 mm	

Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
1	Red cone 15 deg 48600923	2	6x10x0.30
		1	6x16x0.25
1	Spring C=50N/mm 48601819	1	6x10x0.30
		1	6x12x0.10
		1	6x13x0.10
		1	6x14x0.10
		1	6x16x0.10
Flow	closed=20-25l/min	1	T6x20x0.10
		1	6x12x0.10
Flow	open=45-50l/min	3	T6x20x0.10
		1	6x18x0.10
Wechselventil Hubhöhe / check valve lift height			

PC

KTM/HQV/GG Cross Country 125 Race

Artikelnummer /
Article number

A460C171Y403200

Reservoir Federrate / reservoir spring rate	12 (48601588)	N/mm	Öl Viskosität / oil viscosity	SAE 4
Ölmenge (Gabelholm) / oil capacity (fork leg)	400	ml	Federweg / fork stroke	309 mm
Ölmenge (Cartridge) / oil capacity (cartridge)	175	ml	Gabellänge / fork length	950 mm

Einstellung / adjustment	Gewicht Fahrer / riders weight	Feder Bezeichnung / spring description	Federlänge mit Büchse / spring length with spacer	Teilenummer / part.-no.
Weich Opt. 2 / soft opt. 2	55-65 kg 121-143 lb	(43,2) 4,2-485	488 mm	91410114
Weich Opt. 1 / soft opt. 1	65-75 kg 143-165 lb	(43,2) 4,4-485	488 mm	91410115
STANDARD	75-85 kg 165-187 lb	(43,2) 4,6-485	488 mm	91410116
Hart Opt. 1 / hard opt. 1	85-95 kg 187-209 lb	(43,2) 4,8-485	488 mm	91410117
Hart Opt. 2 / hard opt. 2	95-105 kg 209-232 lb	(43,2) 5,0-485	488 mm	91410118

Shims Kolben Midvalve /
shims piston midvalve

Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
1	T6x22x0.10	1	8x26x0.40
2	6x19x0.10	Nut	48601260
1	6x18x0.10		
1	6x16x0.10		
1	6x14x0.10		
1	6x12x0.10		
1	42601262		
1	6x12x0.25		
1	6x14x0.15		
1	6x16x0.15		
1	6x18x0.15		
1	6x20x0.15		
1	6x22x0.15		
1	6x24x0.15		
1	6x14x0.10		
3	6x26x0.10		
Wechselventil Hubhöhe / check valve lift height		1,0 mm	

[illegible]

PC

KTM/HQV/GG Cross Country 250/300 2T Comfort

A460C173Y403200

Shims Kolben Midvalve / shims piston midvalve			
Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
1	Red cone 15 deg 48600923	2	6x10x0.30
		1	6x16x0.25
1	Spring C=50N/mm 48601819	1	6x10x0.30
		1	6x12x0.10
		1	6x14x0.10
		1	6x16x0.10
		1	T6x20x0.10
Flow	closed=20-25l/min	1	6x12x0.10
		3	T6x20x0.10
Flow	open=45-50l/min	1	6x18x0.10
Wechselventil Hubhöhe / check valve lift height			

PC

KTM/HQV/GG Cross Country 250/300 2T Race

Artikelnummer /
Article number

A460C173Y403200

Reservoir Federrate / reservoir spring rate	12 (48601588)	N/mm	Öl Viskosität / oil viscosity	SAE 4
Ölmenge (Gabelholm) / oil capacity (fork leg)	400	ml	Federweg / fork stroke	309 mm
Ölmenge (Cartridge) / oil capacity (cartridge)	175	ml	Gabellänge / fork length	950 mm

Einstellung / adjustment	Gewicht Fahrer / riders weight	Feder Bezeichnung / spring description	Federlänge mit Büchse / spring length with spacer	Teilenummer / part.-no.
Weich Opt. 2 / soft opt. 2	55-65 kg 121-143 lb	(43,2) 4,4-485	488 mm	91410115
Weich Opt. 1 / soft opt. 1	65-75 kg 143-165 lb	(43,2) 4,6-485	488 mm	91410116
STANDARD	75-85 kg 165-187 lb	(43,2) 4,6-485	488 mm	91410116
Hart Opt. 1 / hard opt. 1	85-95 kg 187-209 lb	(43,2) 4,8-485	488 mm	91410117
Hart Opt. 2 / hard opt. 2	95-105 kg 209-232 lb	(43,2) 5,0-485	488 mm	91410118

**Shims Kolben Midvalve /
shims piston midvalve**

Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
1	T6x22x0.10	1	8x26x0.40
2	6x19x0.10	Nut	48601260
1	6x18x0.10		
1	6x16x0.10		
1	6x14x0.10		
1	6x12x0.10		
1	6x10x0.10		
1	48601262		
1	6x12x0.25		
1	6x14x0.15		
1	6x16x0.15		
1	6x18x0.15		
1	6x20x0.15		
1	6x22x0.15		
1	6x24x0.15		
1	6x14x0.10		
3	6x26x0.10		
Wechselventil Hubhöhe / check valve lift height	1,0 mm		

[illegible]

PC

KTM/HQV/GG Cross Country 250 4T Comfort

Artikelnummer /
Article number

A460C175Y403200

[illegible]

PC

KTM/HQV/GG Cross Country 250 4T Race

A460C175Y403200

[illegible]

PC

KTM/HQV/GG Cross Country 350 4T Comfort

Artikelnummer /
Article number

A460C177Y403200

[illegible]

PC

KTM/HQV/GG Cross Country 350 4T Race

**Artikelnummer /
Article number**

A460C177Y403200

Shims Kolben Midvalve / shims piston midvalve			
Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
1	Red cone 15 deg 48600923	1	48601262
		1	6x10x0.10
1	Spring C=50N/mm 48601819	1	6x12x0.10
		1	6x14x0.10
		1	6x16x0.10
		1	T6x20X0.10
		1	6x12x0.10
Flow	closed=20-25l/min	3	T6x20X0.10
		1	6x18x0.10
Flow	open=45-50l/min		
Wechselventil Hubhöhe / check valve lift height			

PC

KTM/HQV/GG Cross Country 450 4T Comfort

Artikelnummer /
Article number

A460C179Y403200

Reservoir Federrate / reservoir spring rate	12 (48601588)	N/mm	Öl Viskosität / oil viscosity	SAE 4
Ölmenge (Gabelholm) / oil capacity (fork leg)	400	ml	Federweg / fork stroke	309 mm
Ölmenge (Cartridge) / oil capacity (cartridge)	175	ml	Gabellänge / fork length	950 mm

Einstellung / adjustment	Gewicht Fahrer / riders weight	Feder Bezeichnung / spring description	Federlänge mit Büchse / spring length with spacer	Teilenummer / part.-no.
Weich Opt. 2 / soft opt. 2	55-65 kg 121-143 lb	(43,2) 4,4-485	488 mm	91410115
Weich Opt. 1 / soft opt. 1	65-75 kg 143-165 lb	(43,2) 4,6-485	488 mm	91410116
STANDARD	75-85 kg 165-187 lb	(43,2) 4,8-485	488 mm	91410117
Hart Opt. 1 / hard opt. 1	85-95 kg 187-209 lb	(43,2) 5,0-485	488 mm	91410118
Hart Opt. 2 / hard opt. 2	95-105 kg 209-232 lb	(43,2) 5,2-485	488 mm	91410119

**Shims Kolben Midvalve /
shims piston midvalve**

Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
1	T6x22x0.10	1	8x26x0.40
2	6x20x0.10	Nut	48601260
1	6x18x0.10		
1	6x16x0.10		
1	6x14x0.10		
1	6x12x0.10		
1	48601262		
1	6x12x0.25		
1	6x14x0.15		
1	6x16x0.15		
1	6x18x0.15		
1	6x20x0.15		
1	6x22x0.15		
1	6x24x0.15		
1	6x14x0.10		
3	6x26x0.10		
Wechselventil Hubhöhe / check valve lift height		1,0 mm	

[illegible]

PC

KTM/HQV/GG Cross Country 450 4T Race

A460C179Y403200

[illegible]